

■セクションガイド

特徴	電力回生式・ 双方向DC		大容量 高電圧・大電流			コンパクト 高効率 ワイドレンジ	薄型 堅牢性・高 信頼性	高機能 ワイドレン ジ	薄型 高力率・高 機能	コンパクト 高機能 ワイドレンジ	コンパクト 低コスト・ 高精度	ベンチトッ プ型
シリー ズ名	NEW PSB10000 PSB10000JP	NEW PSB9000 PSB9000JP	NEW PSI10000	PSI9000 3U	SG	Asterion DC	DCS	PSI9000 2U	XG	PSI9000DT PSI9000T	DLM600	XEL
												
電圧	0-2000V	0-1500V	0-2000V	0-1500V	0-1000V	0-60V	0-600V	0-750V	0-600V	0-750V	0-300V	0-250V
電流	±5000A	0-±1800A	0-5000A	0-2400A	0-1200A	0-125	0-350A	0-120A	0-220A	0-60A	0-75A	0-5A

容量												
1MW	15-1080kW	2.5-300kW	30-1080kW	5-300kW	4-150kW	1.7kW-5kW	1-3kW	1-3kW	850W-1.7kW	320W-1.5kW	600W	75-180W
300kW												
150kW												
30kW												
10kW												
5kW												
4kW												
3kW												
2kW												
1.5kW												
1kW												
850W												
600W												
320W												
200W												